

## WPB 13-125 Quick DS (600437420) Angle grinder Cardboard box

Order no. 600437420 EAN 4061792181915



Representative picture


















- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for the highest user protection: patented, mechanical disc brake stops the disc after switching off within 2 seconds, even in the event of a power cut
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values		
Parameters		
Amps	12 AMPS	
Grinding wheel Ø	5 "	
Output power	850 W	
No-load speed	11000 RPM	
Revolutions at rated load	8000 RPM	
Torque	30.1 in-lbs	
Spindle thread	5/8" - 11 UNC	
Weight (without power cable)	5.7 lbs	
Cable length	8 ft	
Vibration		
Surface grinding	6 m/s²	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Grinding with sandpaper	2.5 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	93 dB(A)	
Sound power level (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

## Scope of delivery

Guard

Inner support flange

M-Quick flange nut

Side handle Metabo VibraTech (MVT)

www.metabo.com 2 / 2