

## WEV 17-125 Quick Inox (600517420) Angle grinder Cardboard box

Order no. 600517420  
EAN 4061792176249



Representative picture



- Perfect processing of stainless steel: robust, powerful angle grinder with high gear reduction and highly reduced, adjustable speed for cool finish
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

Amps	14.5 AMPS
Grinding wheel Ø	5 "
Rated input power	1700 W
Output power	1040 W
No-load speed	2000 - 7600 RPM
Revolutions at rated load	7600 RPM
Torque	44 in-lbs
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	5.5 lbs
Cable length	8 ft

### Vibration

Surface grinding	4.7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Polishing	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
Inner support flange  
M-Quick flange nut  
Side handle Metabo VibraTech (MVT)