

RSEV 17-125 (603829620) Renovation grinders MetaLoc

Order no. 603829620
EAN 4061792177246



Representative picture



- For effective spot sanding and removal of concrete, screed and coatings with diamond cup wheels
- Universally applicable system for low-dust grinding indoors and outdoors
- Anti-static suction guard can be removed without tools for use on an Angle Grinder with Guard
- High torque and overload capacity for demanding applications in continuous use
- Fast work progress thanks to powerful, robust Metabo Marathon-Motor
- Low weight, ideal for sanding walls and ceilings
- Working close to edges thanks to integrated folding segment
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Metabo S-automatic torque limiting clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly.
- Low vibration side handle Metabo VibraTech (MVT)

Technical values

Parameters

Amps	14.5 AMPS
Cup wheel Ø	5 "
No-load speed	2800 - 9600 RPM
Rated input power	1700 W
Output power	1040 W
Revolutions at rated load	9600 RPM
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	6 lbs
Cable length	13 ft

Vibration

Surface grinding	5.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Side handle Metabo VibraTech (MVT)
Extraction hood GED 125
Inner support flange
Nut with two holes
Diamond cup grinding wheel concrete "classic"
Spanner wrench
MetaLoc case