

METRIC HEX NUTS-DIN 934

- Standard materials: steel, stainless steel.
- Standard plating options: plain & zinc.
- Class 6 are to be used with screws/bolts of property class 6.8 or lower; commonly with machine screws.
- Class 8 are to be used with screws/bolts of property class 8.8 or lower; commonly in automotive and electrical.
- Class 10 are to be used with screws/bolts of property class 10.9 or lower; commonly in farm equipment.

SIZE	THREAD PITCH	WIDTH ACROSS FLATS		THICKNESS OF HEX NUTS	
		Max	Min	Max	Min
M2	0.4	4	3.82	1.6	1.35
M2.5	0.45	5	4.82	2	1.75
М3	0.50	5.5	5.32	2.4	2.15
M4	0.7	7	6.78	3.2	2.9
M5	0.8	8	7.78	4	3.7
M6	1	10	9.78	5	4.7
M8	1.25	13	12.73	6.5	6.14
M10	1.5	17	16.73	8	7.64
M12	1.75	19	18.67	10	9.64
M16	2	24	23.67	13	12.3
M20	2.5	30	29.16	16	14.9

Michigan

400 N. Clinton St.

Stockbridge, MI 49285

Phone: 517-851-8757

Fax: 517-851-7722

Tennessee

3100 Ambrose Ave.

Nashville, TN 37207

Fax: 615-352-6722

Phone: 615-352-6701

Wisconsin

Milwaukee, WI 53220

Phone: 414-344-8034

www.hybrocosales.com