



1000 Watt Electronic Two-Speed Impact Drill SBEV 1000-2

- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for Speed Preselection
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Metabo Longlife-motor with dust protection for long service life
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Restart protection: prevents unintentional start-up after power supply interruption
- Cable-protecting ball joint for optimal freedom of motion when working

| | |
|-----------|---------------|
| Order no. | 600783620 |
| EAN code | 4007430315113 |

| | |
|-------------------------------------|---------------------------|
| Rated input power | 1.010 W |
| Output power | 560 W |
| Maximum torque | 40 / 14 Nm |
| Drill-Ø masonry | 22 mm |
| Drill-Ø concrete | 20 mm |
| Drill Ø steel | 16 / 10 mm |
| Drill-Ø soft wood | 40 / 25 mm |
| No-load speed | 0 - 1.000 / 0 - 2.800 rpm |
| Revolutions at rated load | 1.000 / 2.800 rpm |
| Maximum impact rate | 53.200 bpm |
| Gears | 2 |
| Chuck capacity | 1,5 - 13 mm |
| Collar diameter | 43 mm |
| Drill spindle with hexagonal recess | 6,35 mm |
| Drill spindle thread | 1/2 " - 20 UNF |
| Chuck clamping type | Geared Chucks |
| Weight (without power cable) | 2,7 kg |
| Cable length | 4 m |

Scope of delivery

Geared Chucks, Chuck Keys, rubber-coated side handle, Drilling depth guide, Plastic carry case